

References

- [1] C. Elachi, *Introduction to the Physics and Techniques of Remote Sensing*, New York, NY: John Wiley & Sons, 1987.
- [2] J. Wertz and W. Larson, *Space Mission Analysis and Design*, 3rd ed., El Segundo, CA: Microcosm Press, 1999.
- [3] PMC Quarterly Review Briefing, February 20, 2002.
- [4] E. Croke, J. Schulman, D. Chow, H. Dunlap, K. Holabird, M. Morgan, and S. Weinreb, "New tunnel diode for zero-bias direct detection for millimeter-wave imagers," *SPIE Intl. Symp. on Aerospace/Defense Sensing, Simulation, and Controls*, Orlando, FL, 2001.
- [5] J. Schulman, S. Thomas, D. Chow, E. Croke, H. Dunlap, K. Holabird, W. Clark, and M. Morgan, "High-frequency performance of Sb-heterostructure millimeter-wave diodes: Sb-heterostructure diodes for high-frequency radiometric applications," *14th Indium Phosphide and Related Materials Conference*, Stockholm, 2002.
- [6] J. Schulman, J. Zinck, S. Skeith, S. Thomas, D. Chow, E. Croke, H. Dunlap, K. Holabird, M. Morgan, and S. Weinreb, "Physics of Sb-heterostructure quantum tunneling millimeter-wave diodes," *44th Electron Materials Conference*, Santa Barbara, CA, 2002.
- [7] A. Mellberg, N. Wadefalk, N. Rorsman, E. Choumas, J. Stenarson, I. Angelov, P. Starski, E. Kollberg, J. Grahn, and H. Zirath, "InP HEMT-based, cryogenic, wideband LNAs for 4-8 GHz operating at very low DC-power," *14th Indium Phosphide and Related Materials Conference*, Stockholm, 2002.
- [8] Arecibo Observatory Home Page, www.naic.edu
- [9] NRAO Very Large Array Home Page, www.aoc.nrao.edu/vla/html/VLAhome.shtml
- [10] The Atacama Large Millimeter Array Web Site, www.mma.nrao.edu
- [11] SETI Institute, www.seti-inst.edu/Welcome.html
- [12] ASTRON Homepage, www.astron.nl/skai
- [13] Deep Space Network Homepage, deepspace.jpl.nasa.gov/dsn
- [14] S. Weinreb, "Study of an array of small antennas for space communication applications," JPL presentation, April 16, 2001.
- [15] S. Weinreb, "Technology and applications of large microwave arrays," Caltech presentation, May 13, 2002.
- [16] M. Morgan and S. Weinreb, "A full waveguide band MMIC tripler for 75-110 GHz," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 103-106, Phoenix, AZ, 2001.
- [17] P. Penfield and R. Rafuse, *Varactor Applications*, Cambridge, MA: MIT Press, 1962.
- [18] S. Maas, *Nonlinear Microwave Circuits*, New York, NY: IEEE Press, 1997.
- [19] S. Chen, T. Ho, F. Phelleps, J. Singer, K. Pande, P. Rice, J. Adair, and M. Ghahremani, "A high-performance 94-GHz MMIC doubler," *IEEE Microwave Guided Wave Lett.*, vol. 3, pp. 167-169, June 1993.
- [20] J. Papapolymerou, F. Bauchler, J. East, and L. Katehi, "W-band Finite Ground Coplanar monolithic multipliers," *IEEE Trans. Microwave Theory and Tech.*, vol. MTT-47, pp. 614-619, May 1999.
- [21] "Fullband Frequency Triplers," Product data sheet, REV00 C 051199, Millitech Corporation, Technology and Manufacturing Center, South Deerfield, MA.
- [22] "Frequency Multipliers," Product data sheet, Pacific Millimeter Products, Golden, CO.
- [23] M. Cohn, R. Freitag, H. Henry, J. Degenford, and D. Blackwell, "A 94 GHz MMIC tripler using anti-parallel diode arrays for idler separation," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 763-766, San Diego, CA, 1994.
- [24] A. Rahal, R. Bososio, C. Rogers, J. Ovey, M. Sawan, and M. Missous, "A W-band medium power multi-stack quantum barrier varactor tripler," *IEEE Microwave Guided Wave Lett.*, vol. 5, pp. 368-370, November 1995.

- [25] Y. Campos-Roca, L. Verweyen, M. Fernandez-Barciela, E. Sanchez, M.C. Curras-Francos, W. Bronner, A. Hulsmann, and M. Schlechtweg, "An optimized 25.5-76.5 GHz PHEMT-based coplanar frequency tripler," *IEEE Microwave Guided Wave Lett.*, vol. 10, pp. 242-244, June 2000.
- [26] H. Fudem, and E. Niehenke, "Novel millimeter-wave active MMIC triplers," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 387-390, Baltimore, MD, 1998.
- [27] A. Raisanen, "Frequency multipliers for millimeter and submillimeter wavelengths," *Proc. IEEE*, vol. 80, pp. 1842-1852, November 1992.
- [28] K. Lin, H. Wang, M. Morgan, T. Gaier, and S. Weinreb, "A W-band GCPW MMIC diode tripler," *32nd European Microwave Conference*, Milan, 2002.
- [29] V. Radisic, M. Micovic, M. Hu, P. Janke, C. Ngo, L. Nguyen, L. Samoska, and M. Morgan, "164-GHz MMIC HEMT doubler," *IEEE Microwave and Wireless Components Letters*, vol. 11, pp. 241-243, June 2001.
- [30] M. Morgan and S. Weinreb, "A monolithic HEMT diode balanced mixer for 100-140 GHz," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 99-102, Phoenix, AZ, 2001.
- [31] S. Maas, *Microwave Mixers*, 2nd ed. Boston, MA: Artech House, 1993.
- [32] Y. L. Kok, H. Wang, M. Barsky, R. Lai, M. Sholley, and B. Allen, "A 180-GHz monolithic sub-harmonic InP-based HEMT diode mixer," *IEEE Microwave Guided Wave Lett.*, vol. 9, pp. 529-531, December 1999.
- [33] K. Chang, H. Wang, K. Tan, S. Bui, T. Chen, G. Dow, J. Berenz, T. Ton, D. Garske, T. Lin, and L. Liu, "A W-band monolithic downconverter," *IEEE Trans. Microwave Theory and Tech.*, vol. 39, pp. 1972-1979, December 1991.
- [34] Y. Kok, P. Huang, H. Wang, B. Allen, R. Lai, M. Sholley, T. Gaier, and I. Mehdi, "120 and 60 GHz monolithic InP-based HEMT diode sub-harmonic mixer," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 1723-1726, Baltimore, MD, 1998.
- [35] W. Menzel, "A 140-GHz balanced mixer for finline integrated-circuits," *Microwaves & RF*, p. 34, 1983.
- [36] R. Tahim, K. Chang, and K. Hummer, "Wideband microstrip balanced mixer," *Electronics Letters*, vol. 23, pp. 767-768, July 1987.
- [37] Y. C. Leong and S. Weinreb, "Synthesis of broadband TEM coupled line phase shifters," submitted.
- [38] Y. C. Leong and S. Weinreb, "Novel technique of phase velocity equalization for microstrip coupled-line phase shifters," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 1453-1456, Boston, MA, 2000.
- [39] R. Lai, M. Barsky, T. Huang, M. Sholley, H. Wang, Y. Kok, D. Streit, T. Block, P. Liu, T. Gaier, and L. Samoska, "An InP HEMT MMIC LNA with 7.2-dB gain at 190 GHz," *IEEE Microwave Guided Wave Lett.*, vol. 8, pp. 393-395, Nov. 1998.
- [40] Environmental Monitoring page, <http://www.trexenterprises.com/environ.html>
- [41] A. Anastassiou and M. Strutt, "Effect of source lead inductance on the noise figure of GaAs FET," *Proc. IEEE*, vol. 62, pp. 406-408, March 1974 (corr. S. Iversen, *Proc. IEEE*, vol. 63, pp. 983-984, June 1975).
- [42] J. Lange, "Noise characterization of linear twoports in terms of invariant parameters," *IEEE Journal of Solid State Circuits*, vol. 2, pp. 37-40, June 1967.
- [43] M. Pospieszalski, "Modeling of noise parameters of MESFET's and MODFET's and their frequency and temperature dependence," *IEEE Trans. Microwave Theory and Tech.*, vol. 37, pp. 1340-1350, September 1989.
- [44] S. Cripps, *RF Power Amplifiers for Wireless Communications*, Norwood, MA: 1999.
- [45] S. Kee, I. Aoki, A. Hajimiri, and D. Rutledge, "The class E/F family of ZVS switching amplifiers," *IEEE Trans. Microwave Theory and Tech.*, vol. 51, May 2003.
- [46] L. Samoska and Y. Leong, "65-145 GHz InP HEMT medium power amplifiers," *IEEE MTT-S Intl. Microwave Symp. Dig.*, pp. 1805-1808, Phoenix, AZ, 2001.
- [47] M. Morgan and S. Weinreb, "A W-band monolithic medium power amplifier," *IEEE MTT-S Intl. Microwave Symp.*, Philadelphia, PA, 2003.
- [48] D. Ingram, Y. Chen, J. Kraus, B. Brunner, B. Allen, H. Yen, and K. Lau, "A 427 mW, 20% compact W-band InP HEMT MMIC power amplifier," *IEEE RFIC Symp. Dig.*, pp. 95-98, June 1999.

- [49] M. Matloubian, P. Petre, L. Hamilton, R. Bowen, M. Lui, H. Sun, C. Ngo, P. Janke, D. Baker, R. Robertson, "W-band InP HEMT MMICs using finite-ground coplanar waveguide (FGCPW) design," *IEEE Journal of Solid-State Circuits*, vol. 34, pp. 1212-1218, September 1999.
- [50] S. Ortiz, J. Hubert, L. Mirth, E. Schlecht, A. Mortazawi, "A high-power Ka-band quasi-optical amplifier array," *IEEE Trans. Microwave Theory and Tech.*, vol. 50, pp. 487-494, February 2002.
- [51] G. Gonzalez, *Microwave Transistor Amplifier: Analysis and Design*, 2nd ed., Upper Saddle River, NJ: Prentice Hall, 1997.
- [52] J. Rollett, "Stability and power-gain invariants of linear twoports," *IRE Trans. Circuit Theory*, vol. 9, pp. 29-32, March 1962.
- [53] R. Meys, "Review and discussion of stability criteria for linear 2-ports," *IEEE Trans. Circuits and Systems*, vol. 37, pp. 1450-1452, November 1990.
- [54] G. Lombardi and B. Neri, "Criteria for the evaluation of unconditional stability of microwave linear two-ports: a critical review and new proof," *IEEE Trans. Microwave Theory and Tech.*, vol. 47, pp. 746-751, June 1999.
- [55] L. Samoska, K. Lin, H. Wang, Y. Chung, M. Aust, S. Weinreb, and D. Dawson, "On the stability of millimeter-wave power amplifiers," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 429-432, Seattle, WA, 2002.
- [56] M. Morgan and S. Weinreb, "A millimeter-wave perpendicular coax-to-microstrip transition," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 817-820, Seattle, WA, 2002.
- [57] E. England, "A coaxial to microstrip transition," *IEEE Trans. Microwave Theory and Tech.*, vol. MTT-24, pp. 47-48, January 1976.
- [58] R. Eisenhart, "Electrical coupler," U.S. Patent: 4,280,112, July 1981.
- [59] R. Neidert, "Waveguide-to-coax-to-microstrip transitions for millimeter-wave monolithic circuits," *Microwave Journal*, vol. 26, June 1983.
- [60] J. Chenkin, "DC to 40 GHz coaxial-to-microstrip transition for 100 μm thick GaAs substrates," *IEEE Trans. Microwave Theory and Tech.*, vol. 37, July 1989.
- [61] J. Browne, "Coax test fixture checks microstrip circuits to 60 GHz," *Microwave & RF*, vol. 28, pp. 136-137, December 1989.
- [62] B. Oldfield, "Connector and termination construction above 50 GHz," *Applied Microwave & Wireless*, pp. 56-66, April 2001.
- [63] "Precision RF and Microwave Components," catalog, 2001 edition, Anritsu Corporation.
- [64] Y. C Leong and S. Weinreb, "Full band waveguide-to-microstrip probe transitions," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 1435-1438, Anaheim, CA, 1999.
- [65] S. Weinreb, T. Gaier, R. Lai, M. Barsky, Y. C. Leong, and L. Samoska, "High-gain 150-215-GHz MMIC amplifier with integral waveguide transitions," *IEEE Microwave Guided Wave Lett.*, vol. 9, pp. 282-284, July 1999.
- [66] UltraSource Inc. - The Thin Film Source, www.ultra-source.com
- [67] ATP: Home, www.thinfilm.com
- [68] American Technical Ceramics - Welcome, www.atceramics.com/index.html
- [69] M. Morgan and S. Weinreb, "Octave-bandwidth high-directivity microstrip codirectional couplers," *IEEE MTT-S Intl. Microwave Symp.*, Philadelphia, PA, 2003.
- [70] S. Uysal, *Nonuniform Line Microstrip Directional Couplers and Filters*, Norwood, MA: Artech House, 1993.
- [71] P. Ikalainen and G. Matthei, "Wideband forward-coupling microstrip hybrids with high-directivity," *IEEE Trans. Microwave Theory and Tech.*, vol. 35, pp. 719-725, August 1987.
- [72] M. Morgan, S. Weinreb, N. Wadefalk, and L. Samoska, "A MMIC-based 75-110 GHz signal source," *IEEE MTT-S Intl. Microwave Symp. Digest*, pp. 1859-1862, Seattle, WA, 2002.
- [73] "Series AMC active multiplier chain," product data sheet rev01 C 021801, Millitech, Northampton, MA.
- [74] "Agilent 83557A/83558A 50 to 75 GHz/75 to 110 GHz mm-wave source modules," product data sheet, Agilent Technologies, Test and Measurement
- [75] *Reference Data for Radio Engineers*, Indianapolis, IN: Howard W. Sams & Co., 1981.
- [76] G. Matthaei, L. Young, and E. Jones, *Microwave Filters, Impedance-Matching Networks, and Coupling Structures*, Dedham, MA: Artech House, 1980.

- [77] N. Erickson, "High performance dual directional couplers for near-mm wavelengths," *IEEE Microwave and Wireless Component Lett.*, vol. 11, pp. 205-207, May 2001.