

Bibliography

- [1] P. Demorest, “A pulsar timing array for gravitational wave detection,” presented at the Building on New Worlds, New Horizons: New Science from Sub-millimeter to Meter Wavelengths, Mar. 2011.
- [2] A. Niell, A. Whitney, B. Petrachenko, W. Schluter, N. Vandenberg, H. Hase, Y. Koyama, C. Ma, H. Schuh, and G. Tuccari. VLBI2010: Current and future requirements for geodetic VLBI systems. IVS Memorandum 2006-008v01. [Online]. Available: <ftp://ivscc.gsfc.nasa.gov/pub/memos/ivs-2006-008v01.pdf>
- [3] B. Petrachenko. VLBI2010 frequency considerations. IVS Memorandum 2008-015v01. [Online]. Available: <ftp://ivscc.gsfc.nasa.gov/pub/memos/ivs-2008-015v01.pdf>
- [4] J. D. Kraus, *Radio Astronomy*, 2nd ed. Powell, OH: Cygnus-Quasar Books, 1986, ch. 8-3 Source Spectra.
- [5] G. E. Jones, “Instrumentation for wide bandwidth radio astronomy,” Ph.D. dissertation, California Institute of Technology, Pasadena, CA, Jun. 2010. [Online]. Available: <http://resolver.caltech.edu/CaltechTHESIS:10122009-094525715>
- [6] P. J. Hall, Ed., *The SKA: An Engineering Perspective*. The Netherlands: Springer, 2005.
- [7] US SKA Consortium, “The square kilometer array preliminary strawman design large N - small D,” SKA Memo 18, Jul. 2002.
- [8] J. Yang, M. Pantaleev, P.-S. Kildal, Y. Karandikar, L. Helldner, N. Wadefalk, and C. Beaudoin, “Cryogenic 2-13 GHz Eleven feed for reflector antennas in future wideband radio telescopes,” *IEEE Trans. Antennas Propag.*, vol. 59, no. 6, pp. 1918–1934, Jun. 2011.
- [9] G. Engargiola and W. J. Welch, “Log-periodic antenna,” U.S. Patent 6 677 913, Jan. 13, 2004.
- [10] R. S. Gawande and R. F. Bradley, “Characterization of the active, inverted, conical sinuous antenna,” in *XXIX General Assembly of URSI*, Chicago, IL, Aug. 2008.
- [11] C. A. Balanis, *Antenna Theory: Analysis and Design*, 3rd ed. New Jersey: Wiley, 2005.

- [12] S. Weinreb, "Low-noise cooled GASFET amplifiers," *IEEE Trans. Microw. Theory Tech.*, vol. MTT-28, no. 10, Oct. 1980.
- [13] J. D. Pandian, L. Baker, G. Cortes, P. F. Goldsmith, A. A. Deshpande, R. Ganesan, J. Hagen, L. Locke, N. Wadefalk, and S. Weinreb, "Low-noise 6-8 ghz receiver," *IEEE Microwave Magazine*, vol. 7, no. 6, Dec. 2006.
- [14] J. Schleeh, G. Alestig, J. Halonen, A. Malmros, B. Nilsson, P. Nilsson, J. Starski, N. Wade-falk, H. Zirath, and J. Grahn, "Ultralow-power cryogenic InP HEMT with miunimum noise temperature of 1 K at 6 GHz," *IEEE Electron Device Lett.*, vol. 33, no. 5, May 2012.
- [15] D.-W. Tu, S. W. Duncan, A. Eskandarian, B. Golja, B. C. Kane, S. P. Svensson, S. Weinreb, and N. E. Byer, "High gain monolithic W-band low noise amplifiers based on pseudomorphic high electron mobility transistors," *IEEE Trans. Microw. Theory Tech.*, vol. 42, no. 12, Dec. 1994.
- [16] M. Varonen, R. Reeves, P. Kangalashti, L. Samoska, A. Akgiray, K. Cleary, R. Gawande, A. Fung, T. Gaier, S. Weinreb, A. C. S. Readhead, C. Lawrence, S. Sarkozy, and R. Lai, "A 75-116 GHz LNA with 23-K noise temperature at 108 GHz," in *submitted to 2013 IEEE International Microwave Symposium*, Seattle, WA, Jun. 2013.
- [17] L. Samoska, M. Varonen, R. Reeves, K. Cleary, R. Gawande, P. Kangalashti, T. Gaier, R. Lai, and S. Sarkozy, "W-band cryogenic InP MMIC LNAs with noise below 30K," in *2012 IEEE MTT-S International Microwave Symposium Digest*, Jun. 2012.
- [18] H. Wang, G. I. Ng, R. Lai, Y. Hwang, D. C. W. Lo, R. Dia, A. Freudenthal, and T. Block, "Fully passivated W-band InAlAs/InGaAs/InP monolithic low noise amplifiers," in *IEE Proceedings Microwaves, Antennas and Propagation*, vol. 143, no. 5, Oct. 1996.
- [19] D. S. Russell, "Technology advances for radio astronomy," Ph.D. dissertation, California Institute of Technology, Pasadena, CA, Jun. 2013. [Online]. Available: <http://resolver.caltech.edu/CaltechTHESIS:11262012-212534634>
- [20] W. R. Deal, K. Leong, V. Radisic, S. Sarkozy, B. Gorospe, J. Lee, P. Liu, W. Yoshida, J. Zhou, M. Lange, R. Lai, and X. B. Mei, "Low noise amplification at 0.67 THz using 30 nm InP HEMTs," *IEEE Microw. Wireless Compon. Lett.*, vol. 21, no. 7, Jul. 2011.
- [21] W. R. Deal, X. B. Mei, V. Radisic, K. Leong, S. Sarkozy, B. Gorospe, J. Lee, P. Liu, W. Yoshida, J. Zhou, M. Lange, J. Uyeda, and R. Lai, "Demonstration of a 0.48 THz amplifier module using InP HEMT transistors," *IEEE Microw. Wireless Compon. Lett.*, vol. 20, no. 5, May 2010.

- [22] A. Tessmann, M. Kuri, M. Riessle, H. Massler, M. Zink, W. Reinert, W. Bronner, and A. Leuther, “A compact W-band dual-channel receiver module,” in *2006 IEEE MTT-S International Microwave Symposium Digest*, Jun. 2006.
- [23] C. Schwörer, A. Tessmann, A. Leuther, H. Massler, W. Reinert, and M. Schlechtweg, “Low-noise W-band amplifiers for radiometer applications using a 70nm metamorphic HEMT technology,” in *European Gallium Arsenide and other Compound Semiconductors Application Symposium*, Oct. 2003.
- [24] W. Ciccognani, E. Limiti, P. Longhi, and M. Renvoise, “MMIC LNAs for radioastronomy applications using advanced industrial 70 nm metamorphic technology,” *IEEE J. Solid-State Circuits*, vol. 45, no. 10, Oct. 2010.
- [25] R. C. Johnson and H. Jasik, *Antenna Engineering Handbook*, 2nd ed. New York: McGraw-Hill, 1984.
- [26] S. Ramo, J. R. Whinnery, and T. V. Duzer, *Fields and Waves in Communication Electronics*, 3rd ed. John Wiley & Sons, 1994.
- [27] D.-W. Duan and Y. Rahmat-Samii, “A generalized three-parameter aperture distribution for antenna applications,” *IEEE Trans. Antennas Propag.*, vol. 40, no. 6, pp. 697–713, Jun. 1992.
- [28] A. C. Ludwig, “Antenna feed efficiency,” Jet Propulsion Laboratory/NASA, Pasadena, CA, USA, Space Programs Summary 37-26, vol. IV, Apr. 1964.
- [29] ——, “Radiation pattern synthesis for circular aperture horn antennas,” *IEEE Trans. Antennas Propag.*, vol. AP-14, no. 4, pp. 434–440, Jul. 1966.
- [30] P.-S. Kildal, *Foundations of Antennas A Unified Approach*. Lund, Sweden: Studentlitteratur, 2000.
- [31] R. E. Collin, “Aperture efficiency for paraboloidal reflectors,” *IEEE Trans. Antennas Propag.*, vol. AP-32, Sep. 1984.
- [32] P.-S. Kildal, “Factorization of the feed efficiency of paraboloids and cassegrain antennas,” *IEEE Trans. Antennas Propag.*, vol. AP-33, Aug. 1985.
- [33] A. C. Ludwig, “The definition of cross polarization,” *IEEE Trans. Antennas Propag.*, vol. 21, Jan. 1973.
- [34] H. M. Pickett, J. C. Hardy, and J. Farhoomand, “Characterisation of a dual-mode horn for submillimetre wavelengths,” *IEEE Trans. Microw. Theory Tech.*, vol. 32, no. 8, Aug. 1984.

- [35] P. D. Potter, "A new horn antenna with suppressed sidelobes and equal beamwidths," *Microwave Journal*, vol. VI, no. 6, Jun. 1963.
- [36] S. B. Cohn, "Properties of ridged wave guide," *Proceedings of the IRE*, vol. 35, Aug. 1947.
- [37] N. Marcuvitz, Ed., *Waveguide Handbook*, ser. MIT Radiation Laboratory. Lexington, MA: Boston Technical, 1964, vol. 10.
- [38] S. Hopfer, "The design of ridged waveguides," *IRE Trans. Microw. Theory Tech.*, vol. 3, Oct. 1955.
- [39] J. P. Montgomery, "On the complete eigenvalue solution of ridged waveguide," *IEEE Trans. Microw. Theory Tech.*, vol. MTT-19, Jun. 1971.
- [40] M. H. Chen, G. N. Tsandoulas, and F. G. Willwerth, "Modal characteristics of quadruple-ridged circular and square waveguides (short papers)," *IEEE Trans. Microw. Theory Tech.*, vol. 22, Aug. 1974.
- [41] W. Sun and C. A. Balanis, "MFIE analysis and design of ridged waveguides," *IEEE Trans. Microw. Theory Tech.*, vol. 41, pp. 1965–1971, Nov. 1993.
- [42] ——, "Analysis and design of quadruple-ridged waveguides," *IEEE Trans. Microw. Theory Tech.*, vol. 42, pp. 2201–2207, Dec. 1994.
- [43] G. M. Coutts, "Octave bandwidth orthomode transducers for the expanded very large array," *IEEE Trans. Antennas Propag.*, vol. 59, no. 6, pp. 1910–1917, Jun. 2011.
- [44] C. Granet and G. L. James, "The quad-ridged omt: The effects of fin shape on performance," CSIRO, Australia, Tech. Rep. RPP 3879, Oct. 1996.
- [45] R. J. Bauerle, R. Schrimpf, E. Gyorko, and J. Henderson, "The use of a dielectric lens to improve the efficiency of a dual-polarized quad-ridge horn from 5 to 15 GHz," *IEEE Trans. Antennas Propag.*, vol. 57, no. 6, pp. 1822–1825, Jun. 2009.
- [46] S. A. Soroka, "A physically compact quad ridge horn design," in *1986 Antennas and Propagation Society International Symposium*, Jun. 1986.
- [47] M. Gilbert, K. Higgins, and L. Romero, "Quad-ridge horn utilizing resistive films to reduce sidelobes," in *2007 IEEE Antennas and Propagation Society International Symposium*, Jun. 2007.
- [48] CST Microwave Studio 2011. Darmstadt, Germany: CST AG, 2011.
- [49] C. Granet, "Profile options for feed horn design," in *2000 Asia-Pacific Microwave Conference*, Sydney, NSW, Australia, Dec. 2000.

- [50] J. Shin and D. H. Schaubert, "A parameter study of stripline-fed Vivaldi notch-antenna arrays," *IEEE Trans. Antennas Propag.*, vol. 47, no. 5, May 1999.
- [51] S. Silver, Ed., *Microwave Antenna Theory and Design*, ser. MIT Radiation Laboratory. London, UK: Peter Peregrinus, 1984, vol. 12.
- [52] Y. Rahmat-Samii, "Chapter 15 - reflector antennas," in *Antenna Handbook*, Y. T. Lo and S. W. Lee, Eds. New York: Van Nostrand Reinhold, 1988.
- [53] MATLAB version 7.10.0. Natick, MA: The Mathworks, Inc., 2010.
- [54] J. L. Doane, *Infrared and Millimeter Waves*. Orlando, FL, USA: Academic Press, 1985, vol. 13 Millimeter-wave Components and Techniques Part IV, ch. 5.
- [55] W. A. Imbriale, S. Weinreb, G. Jones, H. Mani, and A. Akgiray, "The design and performance of a wideband radio telescope for the GAVRT program," *IEEE Trans. Antennas Propag.*, vol. 59, Jun. 2011.
- [56] W. A. Imbriale, "Radio frequency optics design of the 12-meter antenna for the array-based deep space network," Jet Propulsion Laboratory/NASA, Pasadena, CA, USA, IPN Progress Report 42-160, Feb. 2005.
- [57] J. W. M. Baars, P. G. Mezger, and H. Wendker, "The spectra of the strongest non-thermal radio sources in the centimeter-wavelength range," *Astrophysical Journal*, vol. 142, Feb. 1965.
- [58] ——, "The absolute spectrum of Cas A; an accurate flux density scale and a set of secondary calibrators," *Astronomy and Astrophysics*, vol. 61, no. 1, Oct. 1977.
- [59] M. Ott, A. Witzel, A. Quirrenbach, T. P. Krichbaum, K. J. Standke, C. J. Schalinski, and C. A. Hummel, "An updated list of radio flux density calibrators," *Astronomy and Astrophysics*, vol. 284, no. 1, Apr. 1994.
- [60] G. C. Medellin, "Antenna noise temperature calculation," SKA Memo 95, Jul. 2007.
- [61] H. Hase, R. Dassing, T. Klügel, G. Kronschnabl, A. Neidhardt, P. Lauber, R. Kilger, and K. Pausch, "Twin Telescope Wettzell - a VLBI2010 project," presented at the IVS VLBI2010 Workshop on Future Radio Frequencies and Feeds, Wettzell, Germany. [Online]. Available: <http://www.fs.wettzell.de/veranstaltungen/vlbi/frff2009/Part8/ttwvlbi2010e.pdf>
- [62] W. Imbriale, "Faster antenna noise temperature calculations using a novel approximation technique," in *Int. Symp. on Ant. and Prop. and CNC-USNC/URSI Radio Science Meeting*, Toronto, ON, Jul. 2010, pp. 1–4.

- [63] MIT Haystack Observatory Westford radio telescope. [Online]. Available: <http://www.haystack.mit.edu/obs/westford/technical.Wes.html>
- [64] R. Keller, C. Kasemann, S. Weinreb, A. Akgiray, U. Bach, P. Freire, K. Grypstra, R. Karuppusamy, M. Kramer, P. Müller, F. Schäfer, and B. Winkel, “An ultra broad band radiometer receiver for the Effelsberg 100m telescope,” *Advances in Radio Science*, 2013.
- [65] OMMIC, “D007ih small-signal model,” Dec. 2010.
- [66] R. Lai, X. Mei, W. Deal, W. Yoshida, Y. Kim, P. Liu, J. Lee, J. Uyeda, V. Radisic, M. Lange, T. Gaier, L. Samoska, and A. Fung, “Sub 50 nm InP HEMT device with Fmax greater than 1 THz,” in *2007 IEEE International Electron Devices Meeting*, Dec. 2007.
- [67] P. Kangalashti, D. Pukala, T. Gaier, W. Deal, X. Mei, and R. Lai, “Low noise amplifier for 180 GHz frequency band,” in *2008 IEEE MTT-S International Microwave Symposium Digest*, Jun. 2008.
- [68] L. Samoska, A. Fung, D. Pukala, P. Kangalashti, R. Lai, S. Sarkozy, X. Mei, and G. Boll, “On-wafer measurements of S-MMIC amplifiers from 400-500 GHz,” in *2011 IEEE MTT-S International Microwave Symposium Digest*, Jun. 2011.
- [69] M. W. Pospieszalski, “Modeling of noise parameters of MESFETs and MODFETs and their frequency and temperature dependence,” *IEEE Trans. Microw. Theory Tech.*, vol. 37, no. 9, 1989.
- [70] J. C. Bardin, “Silicon-germanium heterojunction bipolar transistors for extremely low-noise applications,” Ph.D. dissertation, California Institute of Technology, Pasadena, CA, Jun. 2009. [Online]. Available: <http://resolver.caltech.edu/CaltechETD:etd-06092009-113849>
- [71] G. Dambrine, H. Happy, F. Danneville, and A. Cappy, “A new method for on wafer noise measurement,” *IEEE Trans. Microw. Theory Tech.*, vol. 41, no. 3, Mar. 1993.
- [72] W. A. Strifler, B. T. Pugh, and R. D. Remba, “Shot noise in GaAs metal semiconductor field effect transistors with high gate leakage current,” *Solid-State Electronics*, vol. 37, no. 10, Sep. 1989.
- [73] J. B. Kuang, P. J. Tasker, G. W. Wang, Y. K. Chen, L. F. Eastman, O. A. Aina, H. Hier, and A. Fathimulla, “Kink effect in submicrometer-gate MBE-grown InAlAs/InGaAs/InAlAs heterojunction MESFET’s,” *IEEE Electron Device Lett.*, vol. 9, no. 12, Dec. 1988.
- [74] B. Georgescu, A. Souifi, G. Post, and G. Guillot, “A slow-trap model for the kink effect on In-AlAs/InP HFET,” presented at the International Conference on Indium Phosphide and Related Materials, May 1997.

- [75] J. L. C. de Diego, "Cryogenic technology in the microwave engineering: Application to MIC and MMIC very low noise amplifier design," Ph.D. dissertation, Universidad de Cantabria, Santander, Spain, May 2010. [Online]. Available: <http://www.tdx.cat/handle/10803/10674>
- [76] R. Reuter, M. Agethen, U. Auer, S. van Waasen, D. Peters, W. Brockerhoff, and F.-J. Tegude, "Investigation and modeling of impact ionization with regard to the RF and noise behavior of HFET," *IEEE Trans. Microw. Theory Tech.*, vol. 45, no. 6, Jun. 1997.
- [77] M. Isler and K. Schünemann, "Impact-ionization effects on the high-frequency behavior of HFETs," *IEEE Trans. Microw. Theory Tech.*, vol. 52, no. 3, Mar. 2003.
- [78] C.-I. Lee, W.-C. Lin, and Y.-T. Lin, "Modeling inductive behavior of MOSFET scattering parameter s_{22} in the breakdown regime," *IEEE Trans. Microw. Theory Tech.*, vol. 60, no. 3, Mar. 2012.
- [79] R. T. Webster, S. Wu, and A. Anwar, "Impact ionization in InAlAs/InGaAs/InAlAs HEMT's," *IEEE Electron Device Lett.*, vol. 21, no. 5, May 2000.
- [80] M. H. Somerville, J. A. del Alamo, and W. Hoke, "Direct correlation between impact ionization and the kink effect in InAlAs/InGaAs HEMT's," *IEEE Electron Device Lett.*, vol. 17, no. 10, Oct. 1996.
- [81] M. H. Somerville, A. Ernst, and J. A. del Alamo, "A physical model for the kink effect in InAlAs/InGaAs HEMT's," *IEEE Trans. Electron Devices*, vol. 47, no. 5, May 2000.
- [82] W. Curtice, "A MESFET model for use in the design of GaAs integrated circuit," *IEEE Trans. Microw. Theory Tech.*, vol. 28, no. 5, May 1980.
- [83] D. Widiger, K. Hess, and J. J. Coleman, "Two-dimensional numerical analysis of the high electron mobility transistor," *IEEE Electron Device Lett.*, vol. 5, no. 7, Jul. 1984.
- [84] A. Materka and T. Kacprzak, "Computer calculation of large-signal GaAs FET amplifier characteristics," *IEEE Trans. Microw. Theory Tech.*, vol. 33, no. 2, Feb. 1985.
- [85] G. Dambrine, A. Cappy, F. Heliodore, and E. Playez, "A new method for determining the FET small-signal equivalent circuit," *IEEE Trans. Microw. Theory Tech.*, vol. 36, no. 7, 1988.
- [86] I. Angelov, H. Zirath, and N. Rosman, "Computer calculation of large-signal GaAs FET amplifier characteristics," *IEEE Trans. Microw. Theory Tech.*, vol. 40, no. 12, Dec. 1992.
- [87] J. Mateos, T. Gonzalez, D. Pardo, V. Hoel, and A. Cappy, "Monte Carlo simulator for the design optimization of low-noise HEMTs," *IEEE Trans. Electron Devices*, vol. 47, no. 10, Oct. 2000.

- [88] D. M. Pozar, *Microwave Engineering*, 2nd ed. USA: John Wiley and Sons, Inc., 1998.
- [89] T. Gaier, P. Kangalashti, and L. Samoska, private communication, 2012.
- [90] J. E. Fernandez, “A noise-temperature measurement system using a cryogenic attenuator,” Jet Propulsion Laboratory/NASA, Pasadena, CA, USA, TPO Progress Report 42-135, Nov. 1998.
- [91] M. W. Pospieszalski, “On the noise parameters of isolator and receiver with isolator at the input,” *IEEE Trans. Microw. Theory Tech.*, vol. MTT-34, no. 4, Apr. 1986.
- [92] ———, “Correction to “On the noise parameters of isolator and receiver with isolator at the input”,” *IEEE Trans. Microw. Theory Tech.*, vol. MTT-34, no. 6, Jun. 1986.
- [93] J. Lange, “Noise characterization of linear twoports in terms of invariant parameters,” *IEEE J. Solid-State Circuits*, vol. SC-2, no. 2, Jun. 1967.
- [94] R. Reeves, private communication, 2013.
- [95] J. Schleeh, private communication, 2013.
- [96] H. Bosma, “On the theory of linear noisy systems,” Ph.D. dissertation, Technical University of Eindhoven, Holland, 1967. [Online]. Available: <http://alexandria.tue.nl/extra3/proefschrift/PRF1A/7706673.pdf>